



ALPE-79-O



Up/Down Architectural LED Linear Pendant



ALPE-79-O is a commercial pendant lighting fixture utilizing an advanced LED optical system to achieve superior performance. The unique design is nearly transparent luminaire when off and excellent uniformity and efficiency when on, reaching 55% downlighting and 45% uplighting distribution, making the illusion of the light floating in mid-air. It has CCT adjustable optional function which is available in 3000K, 3500K and 4000K. It's highly engineered luminaire joining design allows for simple and intuitive assembly in the field without tools which is perfect for applications that include conference rooms, open offices, retail settings, anywhere you want to make a statement.

Features

- UL, cUL Listed, DLC Qualification, Damp Rated
- Available in 4', 6' and 8' length
- Transparent optics
- 0-10V dimming, dim to 10% or 1% options
- 55% downlight and 45% uplight distribution
- Internal & replaceable driver
- CCT adjustable from 3000k, 3500k, 4000k
- Continuous runs



*DesignLights Consortium Qualified and classified for DLC standard / premium, refer to www.designlights.org for details

PERFORMANCE

Dimension	Wattage	Efficacy@4000K	Lumen@4000K
8"x4'	40W	1200lm/ft	4800lm
8"x6' *	60W	1200lm/ft	7200lm
8"x8'	80W	1200lm/ft	9600lm

* 6FT 60W is not DLC qualification.

Lumen output may vary by ±5% based on different CCT and wattage settings. Actual wattage may also vary by ±5%.

Correlated CCT Multiplier	3000K	3500K
Multiplier for Lumen Output	0.95	1.05

Apply to 4000K only in table above to approximate output at other CCT.



ALPE-79-O

Up/Down Architectural LED Linear Pendant

PRODUCT ORDERING GUIDE

Example: ALPE-79-O-4-WH-4800L-D10-80TW

Default Settings: 4000K

ALPE-79-O						
Product Series	Length	Finish	Lumen	0-10V Dim	CRI	CCT
ALPE-79-O Up/Down Linear	4 4 Feet	WH White	4800lm 4ft, up to 4800lm	D10 110-277V AC Dims to 10% <i>Tested Dimmers: Lutron® Diva-Drv, Leviton® IP-710-DL</i>	80 80+ CRI (Standard)	TW CCT adjustable 3000K/3500K/4000K
	6 <i>Make to Order</i> 6 Feet*	BL Black	7200lm <i>Make to Order</i> 6ft, up to 7200lm*		90 <i>Make to Order</i> 90+ CRI*	
	8 8 Feet	CM <i>Make to Order</i> Custom *	9600lm 8ft, up to 9600lm	D01 110-277V AC Dim to 1%		

OPTIONAL PENDANT ACCESSORY

Ceiling Type	Canopy	Power Cord & Aircraft cable	Optional Functions
DW Dry ceiling Mount to J-box	RDWH 1.6" Round & White 4.5" Round & White (Designed for power cable)	C05WH 4 ft white power cord + 5ft aircraft cable	EME Emergency Function (Order separated external LED emergency driver)
TF Drop ceiling clips for 9/16" and 15/16" flat ceiling	SQWH 1.6" Square & White 4.5" Square & White (Designed for power cable)	C12WH 12 ft white power cord + 12ft aircraft cable	OCC Sensor Function (Order separated occupancy sensor that built-in 5.8inch round canopy)
TS Drop ceiling clips for 9/16" slot Ceiling	RDBL 1.6" Round & Black 4.5" Round & Black (Designed for power cable)	C05BL 4 ft black power cord + 5ft aircraft cable	
TX Drop ceiling clips for 15/16" slot Ceiling	SQBL 1.6" Square & Black 4.5" Square & Black (Designed for power cable)	C12BL 12 ft black power cord + 12ft aircraft cable	

CUSTOM LINE ORDERING GUIDE

Example: ALPE-79-O-C18-WH-D10-DW-RDWH-C05WH

CUSTOM LINE (ENTER LENGTH IN FEET)	Finish	0-10V Dim	Ceiling Type	Canopy	Power Cord & Aircraft cable
ALPE-79-O-C__ Up to 8ft Continuous Run Section (Enter length in product code above, ex. C18)	WH White BL Black CM <i>Make to Order</i> Custom *	D10 110-277V AC Dims to 10% <i>Tested Dimmers: Lutron® Diva-Drv, Leviton® IP-710-DL</i> D01 110-277V AC Dim to 1%	DW Dry ceiling Mount to J-box TF Drop ceiling clips for 9/16" and 15/16" flat ceiling TS Drop ceiling clips for 9/16" slot Ceiling TX Drop ceiling clips for 15/16" slot Ceiling	RDWH 1.6" Round & White 4.5" Round & White (Designed for power cable) SQWH 1.6" Square & White 4.5" Square & White (Designed for power cable) RDBL 1.6" Round & Black 4.5" Round & Black (Designed for power cable) SQBL 1.6" Square & Black 4.5" Square & Black (Designed for power cable)	C05WH 4 ft white power cord + 5ft aircraft cable C12WH 12 ft white power cord + 12ft aircraft cable C05BL 4 ft black power cord + 5ft aircraft cable C12BL 12 ft black power cord + 12ft aircraft cable

*Make to Order means additional cost and/or lead time on customized fixtures may apply. Some fixtures require an MOQ. Please contact your sales rep for more information.

Damp rated for ambient operating temperature of -20°C to +40°C [-4° to +104°F]




ALPE-79-O

Up/Down Architectural LED Linear Pendant

MOUNTING


Dry Ceiling / Off Grid

"Various Hard Ceilings" (Mount to J-box)



Drop Ceiling / On Grid

Suspending the luminaire in the T-grid. Compatible for various T-grid, including 9/16" Flat, 9/16" Slot, 15/16" Flat.



*Please see the installation instruction for more details.

Pendant Accessories For Dry Ceiling For 4'

Canopy Kits



Mounting Kits



4FT Standard(12FT Available)



5FT Standard(12FT Available)



Junction Plate

Pendant Accessories For Drop Ceiling For 4'

Canopy Kits



Junction Box



Mounting Kits



4FT Standard
(12FT Available)



5FT Standard
(12FT Available)



Junction Plate

T-grid Clips



For 9/16" and 15/16" Flat Ceiling
(2 Clips/Set)



For 15/16" Slot Ceiling
(2 Clips/Set)



For 9/16" Slot Ceiling
(2 Clips/Set)

Pendant Accessories For Dry Ceiling For 6' or 8'

Canopy Kits



Mounting Kits



4FT Standard(12FT Available)



5FT Standard(12FT Available)



Junction Plate

Pendant Accessories For Drop Ceiling For 6' or 8'

Canopy Kits



Junction Box



Mounting Kits



4FT Standard
(12FT Available)



5FT Standard
(12FT Available)



Junction Plate

T-grid Clips



For 9/16" and 15/16" Flat Ceiling
(2 Clips/Set)



For 15/16" Slot Ceiling
(2 Clips/Set)




For 9/16" Slot Ceiling
(2 Clips/Set)




ALPE-79-O

Up/Down Architectural LED Linear Pendant


Canopy Style



Individual



Continuous Run




The maximum connection of each input line is up to 40FT in 120AC, 100FT in 277AC.

Standard Line Runs In 120V

Luminaire Run Length (ft)	Run Configuration	5' Power Cable	5' Aircraft Cable	Canopy
4	4'	1	2	2
8	8'	1	3	3
12	6'+6'	1	3	3
16	8'+8'	1	5	5
20	8'+8'+4'	1	6	6
24	8'+8'+8'	1	7	7
28	8'+8'+8'+4'	1	8	8
32	8'+8'+8'+8'	1	9	9
36	6'+6'+6'+6'+6'+6'	1	7	7

DIMENSIONS





ALPE-79-O

Up/Down Architectural LED Linear Pendant

OPTIONAL FUNCTION

► Emergency Option

Paraflex offers UL& CEC Listed LED emergency drivers. When AC power fails it, immediately switches to the emergency mode operating for lighting minimum 90 minutes. When AC power is restored it, automatically returns to the charging mode which meets critical life-safety lighting requirements.



EME

Order Separated LED emergency driver

Optional 16w or 25w high voltage LED emergency driver can be provided if you need and do it wiring in field. For more info or spec sheet please visit our, website or contact sales.



Features:

- Field-installable (UL Listed for US & Canada).
- Energy-efficient charger (CEC Title 20 compliant) .
- Premium battery backup – 90+ minutes runtime during outages.
- Backed by a 5-Year Limited Warranty.
- Supports most LED luminaires (Up to 200W).
- Universal input voltage (100–277V AC).
- Automatic self-diagnostic testing with monthly, semi-annual, and annual checkups.

► Occupancy Sensor



OCC


We can provide a factory-installed integrated sensor system for multi-level control based on motion and/or daylight contribution with BRI810-B-D level & daylight harvest microwave sensor from SHARKWARD. For more info or spec sheet, please contact sales.



Specification

Power Supply	120/277 VAC 50/60Hz
Maximum load @-40°F~+158°F (-40°C~+70°C)	Resistive/ Tungsten-600W@120V Electronic Ballast(LED)-800VA@120V/1200VA@277V
HF System	5.8GHz CW
Dim Control Output	0-10V, max.25mA sinking current
Detection Radius/angle	Max 26ft.(8m)/360
Mounting Height	Max 12ft
Humidity	Max.95% RH
Temperature	-40°F~+158°F (-40°C~+70°C)

Sensor Coverage






ALPE-79-O

Up/Down Architectural LED Linear Pendant

DISTRIBUTION DIAGRAM



Zonal Flux Diagram

°	C0	C45	C90	C135	C180
5	605.5	590.4	555.7	525.5	513.5
10	667.7	631.2	557.2	502.3	482.7
15	738.7	675.9	558.8	483.6	460.1
20	816.4	723.2	560.9	469.0	444.8
25	895.5	767.4	562.9	458.4	434.6
30	969.2	807.0	565.0	449.8	427.4
35	1029	838.6	555.6	442.1	420.7
40	1068	858.3	546.1	432.2	412.2
45	1080	848.0	536.7	407.6	400.1
50	1058	821.9	500.2	374.0	383.0
55	998.1	775.5	463.7	332.2	357.8
60	902.1	670.1	427.2	285.2	325.4
65	756.3	547.0	356.5	237.9	279.6
70	563.9	413.1	285.8	187.5	219.7
75	343.7	270.4	215.1	132.7	146.5
80	116.9	138.8	144.0	81.32	54.69
85	2.771	69.37	72.99	41.71	17.09
90	1.200	2.362	1.952	3.282	1.179
95	1.739	55.62	20.43	30.93	9.619
100	264.0	244.5	158.3	97.05	56.23
105	658.9	376.4	236.4	170.5	186.1
110	876.9	500.0	286.2	246.4	258.9
115	972.9	578.6	336.0	301.5	313.2
120	964.2	599.1	385.8	327.6	332.1
125	921.2	599.8	380.0	340.2	342.0
130	815.7	567.5	374.2	329.4	328.9
135	694.5	512.4	368.4	311.9	303.7
140	580.0	470.1	355.2	292.1	277.5
145	526.4	444.4	342.0	287.8	268.6
150	472.9	411.5	328.8	284.1	265.1
155	426.0	389.2	323.1	280.8	264.2
160	382.7	368.5	317.5	284.3	261.7
165	372.3	352.0	311.8	289.9	274.7
170	351.0	340.3	309.9	297.5	287.7
175	327.4	319.2	308.0	304.8	299.0
180	306.1	306.1	306.1	306.1	302.0
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens

°	φ total
0-5	13.29
5-10	53.50
10-15	121.4
15-20	218.2
20-25	344.8
25-30	501.9
30-35	688.6
35-40	901.8
40-45	1137
45-50	1387
50-55	1639
55-60	1882
60-65	2104
65-70	2289
70-75	2428
75-80	2518
80-85	2563
85-90	2577
90-95	2593
95-100	2650
100-105	2770
105-110	2942
110-115	3147
115-120	3368
120-125	3586
125-130	3787
130-135	3963
135-140	4113
140-145	4239
145-150	4344
150-155	4429
155-160	4498
160-165	4551
165-170	4588
170-175	4611
175-180	4618
UNIT: lm	

Luminance cd/(m2)


°(DEG)	C0/180	C90/270
85	132	3489
80	2804	3456
75	5533	3462
70	6870	3481
65	7457	3514
60	7517	3560
55	7251	3368
50	6858	3242
45	6362	3163



ALPE-79-O

Up/Down Architectural LED Linear Pendant

DISTRIBUTION DIAGRAM



Zonal Flux Diagram

°	C0	C45	C90	C135	C180
5	631.9	616.1	580.3	548.6	536.0
10	696.6	659.0	582.0	524.4	503.6
15	770.6	705.7	583.8	504.9	480.3
20	851.6	755.2	586.2	489.8	464.0
25	933.7	801.4	588.5	478.7	453.2
30	1010	842.7	590.9	469.7	445.8
35	1072	875.8	580.8	461.3	438.6
40	1113	896.2	570.8	450.5	429.8
45	1125	885.0	560.7	424.5	417.1
50	1102	857.4	500.2	374.0	383.0
55	1039	808.4	484.7	346.5	373.1
60	936.0	697.9	446.7	297.9	339.1
65	783.1	568.3	372.7	248.8	292.0
70	583.7	427.7	298.7	196.0	228.8
75	352.1	278.5	224.7	138.6	152.4
80	119.9	140.8	150.5	85.01	56.68
85	2.893	70.26	76.27	43.72	16.98
90	1.218	2.470	2.040	3.655	1.261
95	1.805	128.2	83.78	51.46	1.851
100	276.1	256.1	165.5	101.7	56.96
105	685.0	393.7	247.2	179.3	190.5
110	916.6	522.3	299.1	258.8	267.3
115	1014	603.9	351.0	314.9	323.5
120	1005	625.2	402.9	342.4	343.3
125	960.6	625.8	396.7	355.3	354.8
130	847.6	591.9	390.6	344.0	341.9
135	721.1	534.5	384.4	325.9	316.6
140	603.7	490.5	370.6	305.5	289.4
145	548.9	463.3	356.8	300.5	279.7
150	492.7	429.2	343.0	296.5	276.5
155	442.7	406.0	337.1	292.9	275.9
160	398.8	384.2	331.3	296.6	272.8
165	388.4	367.1	325.4	302.4	285.8
170	366.1	354.8	323.4	310.4	299.4
175	341.1	332.9	321.4	318.1	311.1
180	319.4	319.4	319.4	319.4	314.4
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens

°	φ total
0-5	13.87
5-10	55.83
10-15	126.7
15-20	227.7
20-25	359.8
25-30	523.6
30-35	718.3
35-40	940.6
40-45	1186
45-50	1446
50-55	1709
55-60	1963
60-65	2193
65-70	2385
70-75	2530
75-80	2623
80-85	2670
85-90	2684
90-95	2701
95-100	2760
100-105	2886
105-110	3064
110-115	3278
115-120	3509
120-125	3736
125-130	3945
130-135	4129
135-140	4285
140-145	4416
145-150	4525
150-155	4614
155-160	4686
160-165	4741
165-170	4780
170-175	4803
175-180	4811
UNIT: lm	

Luminance cd/(m2)


°(DEG)	C0/180	C90/270
85	138	3646
80	2877	3611
75	5668	3618
70	7111	3639
65	7721	3675
60	7800	3722
55	7551	3521
50	7143	3388
45	6627	3304



ALPE-79-O

Up/Down Architectural LED Linear Pendant

DISTRIBUTION DIAGRAM



Zonal Flux Diagram

°	C0	C45	C90	C135	C180
5	627.5	612.0	576.4	544.9	532.3
10	691.8	654.6	578.2	521.0	500.1
15	765.0	701.1	580.1	501.6	476.9
20	845.2	750.3	582.5	486.7	460.7
25	926.7	796.2	585.0	475.3	450.0
30	1002	837.3	587.5	465.7	442.5
35	1063	870.3	577.6	456.7	435.4
40	1104	890.6	567.7	445.5	426.6
45	1115	879.4	557.8	420.0	414.1
50	1093	852.1	520.0	385.4	396.2
55	1029	803.3	482.2	342.8	370.3
60	925.6	692.3	444.4	295.9	336.2
65	773.9	562.3	370.9	247.2	289.6
70	576.5	421.9	297.3	194.7	227.3
75	351.1	273.8	223.8	137.9	151.6
80	121.6	137.2	149.9	84.87	56.50
85	3.002	68.55	76.00	43.77	16.89
90	1.246	2.661	2.088	3.893	1.280
95	2.216	127.8	83.31	53.39	1.936
100	272.1	255.0	164.5	105.1	55.83
105	679.1	391.9	245.8	176.1	190.5
110	910.0	519.6	297.4	249.3	265.8
115	1007	600.8	349.1	304.9	322.6
120	999.2	622.0	400.7	334.1	349.8
125	954.7	622.6	394.6	349.8	353.2
130	842.5	588.9	388.5	340.2	340.4
135	716.6	531.8	382.5	323.7	315.8
140	600.2	488.1	368.7	303.5	287.9
145	545.6	461.0	354.9	299.0	278.1
150	489.6	426.9	341.2	294.9	274.5
155	439.8	403.6	335.3	291.3	272.9
160	396.5	382.0	329.5	294.8	269.2
165	386.1	365.1	323.6	300.7	282.1
170	364.0	352.8	321.7	308.6	296.2
175	339.4	331.1	319.7	316.3	309.1
180	317.8	317.8	317.8	317.8	312.9
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens

°	φ total
0-5	13.78
5-10	55.45
10-15	125.8
15-20	226.1
20-25	357.2
25-30	519.8
30-35	713.0
35-40	933.6
40-45	1177
45-50	1435
50-55	1696
55-60	1947
60-65	2175
65-70	2366
70-75	2509
75-80	2601
80-85	2647
85-90	2662
90-95	2678
95-100	2737
100-105	2861
105-110	3037
110-115	3249
115-120	3477
120-125	3702
125-130	3910
130-135	4092
135-140	4247
140-145	4378
145-150	4486
150-155	4574
155-160	4645
160-165	4700
165-170	4739
170-175	4762
175-180	4770
UNIT: lm	

Luminance cd/(m2)

°(DEG)	C0/180	C90/270
85	144	3634
80	2917	3597
75	5652	3604
70	7023	3622
65	7630	3656
60	7713	3703
55	7476	3503
50	7083	3371
45	6571	3287

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with Paraflex Industries 2006, Inc. at the time of finalizing the order or design. Paraflex Industries 2006, Inc. does not warrant or represent that the information is free from errors or omission. The information may change without notice and Paraflex Industries 2006, Inc. is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.