EXSE-B

Steel LED Exit Sign


STANDARD | OPTIONAL

LISTED | DAMP LOCATION | MOUNTING CANOPY | SELF DIAGNOSTIC

Steel Exit Sign



Dimensions, inches



Illumination

- Ultra bright, energy efficient, long life Red or Green LEDs exit sign illumination.

Electrical

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting

- Mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

Housing

- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Unique design allows double face conversion in the field.
- Field selectable steel knockout Chevron directional indicators.

Options

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.

Warranty / Listing

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C · 50°C).
- Certified to CEC under Title 20 Regulations.

Ordering Guide

Example: EXSE-B-2-R-W-EM

#	Field	Options
1	**Model**	EXSE-B (steel exit sign)
2	**No. of faces**	2 = Universal single / double face
3	**Letter color**	R = Red G = Green
4	**Housing color**	W = White B = Black
5	**Battery**	(blank) = AC only EM = Battery back-up
6	**Options**	SDT = Self-diagnostics[1]

[1]Available only with EM units

Disclaimer:
Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with Paraflex Industries 2006,Inc. at the time of finalizing the order or design. Paraflex Industries 2006,Inc. does not warrant or represent that the information is free from errors or omission. The information may change without notice and Paraflex Industries 2006,Inc. is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

Paraflex Industries 2006, Inc.
1346 How Lane, North Brunswick, NJ 08902
info@paraflexltg.com
paraflexltg.com